

SAFETY DATA SHEET

	SDS No: 0021
Product Name: NoMark® Plus Trade Name: Film-Stamped ABS Recommended Use: Signage, Other Restrictions on Use: None	
Trade Name: Film-Stamped ABS Recommended Use: Signage, Other Restrictions on Use: None	
Recommended Use: Signage, Other Restrictions on Use: None	
Restrictions on Use: None	
Manufacture: Rowmark In Case 5409 Hamlet Drive	Medcal: 911 e of Emergency: Call: Poison Control: 800-589-3897 Email:
Findlay, OH 45840 Inform	nation: Call: 1-877-ROWMARK
	Email: <u>techhelp@rowmark.com</u>
Section 2. Hazard Identification	
GHS Classification: Not Classified	NEW GHS Hazard Categories
GHS Label Elements: Not Applicable	Category 1 = Severe Hazard
Emergency Overview:	Category 2 = Serious Hazard
APPEARANCE: Various colors; Characteristic odor	Category 3 = Moderate Hazard
	Category 4 = Slight Hazard
Potential Health Effects:	Category 5 = Minimal Hazard
elecated temperatures; contact with the material may cause thermal burn INGESTION: Very low toxicity if swallowed. Harmful effects not anticipated	
INHALATION: Dust may cause irritation to upper repiratory tract (nose and	
GHS Rating	
Health 5	
Flammability 4	
Flammability 4 Instability 5	
Flammability 4 Instability 5 Other 4 HMIS Rating 4 Health 0	
Flammability 4 Instability 5 Other	
Flammability 4 Instability 5 Other	

Other Hazards:	Not Applicable
Section 3.	Composition / Information on Ingredients

Name

% by Weight

Acrylonitrile/butadiene/styrene resin	9003-56-9	90-100%
Aluminium Flake	7429-90-5	1-5%
Carbon Black	1333-86-4	1-5%

May contain the following:		
Mineral Oil	008042-47-5	0-2%
Tallow	008030-12-4	0-2%
Wax	000110-30-5	0-2%

Section 4. First Aid Measures		
Inhalation: Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If r breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.		
Eyes:	Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes. Ge medical attention.	
Skin:	Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool under ice water or a running stream.	
Ingestion:	No adverse health effects expected from ingestion.	

Section 5. Fire-Fighting Mea	asures
Suitable Extinguishing Methods:	Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on
Unsuitable Extinguishing Methods:	NONE known.
Hazards During Fire-fighting:	Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.
Protective Equipment:	Wear self-contained breathing apparatus and protective suit.

Section 6. A	ccidental Release Measures	
Personal Precaution	s: See Section 8 - Exposure Controls / Personal Protection.	
Environmental Prec	autions: No Special environmental precautions required.	
Methods and Materials for Containment and Cleaning Up		
Spill / Leak: Containment of this material should not be necessary. Sweep up or gather material and place in appropria		
If Molten: Allow material to cool and place into an appropriate marked container for disposal.		

Section 7.	Handling and Storage
Handling: Keep away from heat, flame and strong oxidizing agents. Good housekeeping and controlling dusts	
	necessary for safe handling of product. Workers should be protected from the possibility of contact with molten
	resin during fabrication. Large masses of molten polymer held at elevated temperatures for extended periods of
	time may auto-ignite.
Storage:	Keep away from heat, sparks, and flame. Store horizontally in cool, dry place in original container and protect
	from sunlight.

Section 8. Exposure Control and Personal Protection

1) Effects of Acute Exposure:	See section 11, Toxicological Information		
2) Effects of Chronic Over Exposure:	See section 11, Toxicological Information		
3) OSHA Permissible Exposure Limits:	Chemical	OSHA PEL	ACGIH TLV
	Corn Oil	5 mg/m3 (respirable)	None Established
		15 mg/m3 (total) TWA	
	Styrene	100 ppm TWA	20 ppm TWA
		200 ppm Ceiling	20 ppm STEL
		600 ppm Max concentration	
		(5 min in any 3 hrs)	

Engineering Controls:

Use recommended safe	handling practic	es to minimize	unnecessary exposure.
Ose recommended sur	, nununing pructic		unificeessury exposure.

General room ventilation is adequate for storage and ordinary handling.

Use local exhaust at points of fume generation or if dusty conditions prevail.

Personal Protective Equipment:

Wear safety glasses with side shields or chemical goggles to prevent eye contact.

Have eye-washing facilities readily available where eye contact can occur.

Wear impervious gloves and protective clothing to prevent skin contact.

Section 9. Physical and Chemical Properties

Section 5. Thysical and chemical rioperties				
Appearance: Various colors,	Various color	Vapor Pressure:	Not applicable	
Odor:	Slight, sweet, aromatic	Vapor Density:	3.6 (styrene	
pH:	Not applicable	Relative Density:	Approx. 1.05	
Melting Point / Freezing Point:	Not established	Solubility (ies):	Insoluble in water	
Boiling Point:	Not Applicable	Partition Coefficient (N-Octanol/Water):	Not applicable	
Flash Point:	388-400°C (730-752°F)	Auto-Ignition Temperature:	495-510°C (923-950°F)	
Evaporation Rate:	Not Applicable	Decomposition Temperature:	Approx. 260°C (500°F)	
Flammability (solid, gas):	Dust and molten material are flammable	Viscosity:	Not applicable	
Upper Explosive Limit:	Not established	Specific Gravity:	1.05-1.12	
Lower Explosive Limit:	Not established	Percent Volatile:		

Section 10. Stability Reactivity			
Reactivity:	Hazardous polymerization does not occur		
Chemical Stability:	Stable		
Possibility of Hazardous Reactions:	None known		
	Avoid temperatures above 300°C (572°F). Such exposure can cause product to		
Conditions to Avoid:	decompose.		
Incompatible Materials:	None known		
Hazardous Decomposition Products:	Thermal decomposition will generate carbon dioxide, carbon monoxide, styrene, acrylonitrile, hydrogen cyanide, hydrocarbons.		

Combustion Products:

Section 11.	Toxicological Information	
Irritation Effects		
	Eye Irritation:	Solid particles may cause transient irritation from mechanical abrasion.
	Skin Irritation:	Not expected to cause skin irritation. Molten material may cause thermal burns.
	Inhalation:	Not a likely route of exposure. Process fumes may cause irritation.
	Ingestion:	May cause a choking hazard if swallowed.

General Effects of Exposure

Accute Effects of Exposure: Gases and fumes evolved during thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract and cause nausea, drowsiness and headache.

Chronic (non-cancer) Effects of Exposure: Not expected to cause any adverse chronic health effects.

Carcinogenicity:

None of the components present at 0.1% or greater have been classified as a carcinogen.

The Agency for Toxic Substances & Disease Registry concluded in their 2007 Toxicological Profile for Styrene that styrene may possibly be a weak human carcinogen. The EPA has not given a formal carcinogen classification to styrene stating "Several epidemiologic studies suggest there may be an association between styrene exposure and an increased risk of leukemia and lymphoma. However, the evidence is inconclusive due to confounding factors." In 2011 the National Toxicology Program listed styrene as reasonably anticipated to be a human carcinogen based on limited evidence from studies in humans, sufficient evidence from studies in experimental animals, and supporting data on mechanisms of carcinogenesis.

IARC - Overall evaluation: 2B Possible carcinogen
 IARC - Evidence of carcinogenicity in animals: Limited data
 IARC - Evidence of carcinogenicity in humans: Limited data
 NTP - Reasonably anticipated to be a human carcinogen
 ACGIH - A4: Not classifiable as a Human Carcinogen

Product Toxicity Data

Stvrene

Toxicity Note: Toxicity data is based on similar to ABS resins.Skin Irritation: rabbit - non-irritating.Eye Irritation: rabbit - Draize - slightly irritating.

Other Relevant Toxicity Information: Styrene is slightly toxic to practically non-toxic in oral feeding studies (rats) and skin application studies (rabbits). Repeated inhalation studies in rats for 3 weeks reported effects suggestive of a hearing impairment. Repeated inhalation exposures produced lung irritation in guinea pigs and organ weight changes in rats. Styrene caused lung tumors in several strains of mice by inhalation and oral exposure. The evidence in rats is insufficient for reaching a conclusion concerning the carcinogenicity of styrene. There is limited evidence for the carcinogenicity of styrene in humans based on studies of workers that showed an increased mortality from or incidence of cancer of the lymphohematopoietic system and increased levels of DNA adducts and genetic damage in lymphocytes from exposed workers. However, the types of lymphohematopoietic cancer observed in excess varied across different studies and excess risk was not found in all cohorts. In standard mutagenicity tests, both positive and negative results were reported. No birth defects occurred in rats given styrene orally. Some toxic effects on the fetus were noted in a limited inhalation study using repeated high doses.

Toxicity Data for Acrylonitrile/Butadiene/Styrene Terpolymer

Acute Oral Toxicity: LD50 > 5000 mg/kg (rat) Acute Dermal Toxicity: LD50 >2,000 mg/kg (rabbit) estimated Skin Irritation: rabbit – Draize – No skin irritation Eye Irritation: rabbit – Slightly irritating Sensitization: Dermal – non-sensitizer (guinea pig Buehler Test)

Toxicity Data for Styrene

Acute Oral Toxicity: LD50 1000 mg/kg (rat) Acute Inhalation Toxicity: LC50 11.8 mg/L/4 hr (rat) Acute Dermal Toxicity: LD50 >20,000 mg/kg (rabbit) Skin Irritation: rabbit – Draize – moderately irritating Eye Irritation: rabbit – Draize – severely irritating Sensitization: Dermal – non-sensitizer (guinea pig maximization test (GPMT))

Repeated Dose Toxicity

6 months, inhalation NOAEL 6.3 mg/kg (monkey, male/female, daily) 28 Days, dermal NOAEL <500 mg/kg (rat, male daily) 13 weeks, inhalation NOAEL 0.565 mg/L (rat, male/female, daily)

Mutagenicity

Genetic Toxicity in Vitro: Ames: negative (Salmonella typhimurium, metabolic activation with and without) Sister Chromatid Exchange: positive (human lymphocytes, metabolic activation with and without)

Genetic Toxicity in Vivo: Cytogenic assay positive (rat) Drosophila SLRL test: positive (Drosophila melanogaster)

Carcinogenicity

Styrene was tested for carcinogenicity in rats in four gavage studies, one drinking water study and two inhalation studies. Overall, there was no reliable evidence for an increase in tumor incidence in rats in any of these studies. Inhalation exposure caused benign lung tumors (alveolar/bronchiolar adenoma) and increased the combined incidence of benign and malignant lung tumors (alveolar/ bronchiolar adenoma) in CD-1 mice of both sexes; in females, it also increased the separate incidence of malignant lung tumors (alveolar/bronchiolar adenoma and carcinoma) in CD-1 mice of both sexes; in females, it also increased the separate incidence of malignant lung tumors (alveolar/bronchiolar adenoma and carcinoma), and a positive dose-response trend was observed (NCI 1979). These findings are supported by findings of lung tumors in both sexes of O20 mice exposed to styrene (Ponomarkov and Tomatis 1978). In O20 mice, a single dose of styrene was administered to pregnant dams on gestational day 17, and pups were exposed orally once a week for 16 weeks after weaning. A significantly increased incidence and earlier onset of benign and malignant lung tumors combined (adenoma and carcinoma) occurred in mice of both sexes as early as 16 weeks after weaning. In a similar study with C57BI mice administered a much lower dose of styrene, lung-tumor incidence was not significantly increased risks for lymphatic and hematopoietic neoplasms observed in some human epidemiological studies are generally small, statistically unstable and are not very robust.

Toxicity to Reproduction/Fertility

Three generation study, oral, daily (rat, male/female) NOAEL (parental): 250 ppm, NOAEL (F1): 125 ppm, NOAEL (F2): 125 ppm No effects on reproductive parameters observed at doses tested.

Other method, inhalation, daily, (rabbit female) NOAEL parental 2.6 mg/L, NOAEL (F1) 2.6 mg/L

Developmental Toxicity/Teratogenicity

Rat, female inhalation, gestation NOAEL (teratogenicity): >600 ppm, NOAEL (maternal) : <300 ppm. No teratogenic effects observed at doses tested.

Rabbit, female, inhalation, daily, gestation, NOAEL (teratogenicity): >600 ppm, NOAEL (maternal) : >600 ppm. Fetotoxicity seen only with maternal toxicity.

Additional Toxicological Information

When used and handled according to specifications, the product does not have any harmful effects according to research and information provided by suppliers.

Carcinogenic Effect

International Agency for Research on Cancer (IARC) : Group3 NOT classifiable as to its carcinogenicity to humans.

Section 12. Ecological Information		
Eco-toxicity:	Toxicity to fish - No relevant studies identified.	
Persistence and Degradability:	This material is not expected to be readily biodegradable.	
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.	
Mobility in Soil:	This Product has not been found to migrate through soils.	
	This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the	
Other Adverse Effects:	ozone layer.	

Ecological Data for Acrylonitrile/Butadiene/Styrene Terpolymer

Biodegradation:	Not readily biodegradable
Bioaccumulation:	Does not bioaccumulate

Ecological Data for Styrene

Biodegradation:	
Biological Oxygen Demand (BOD):	5 days, 2.46 mg/L
Chemical Oxygen Demand:	2800-2880 mg/g
Theoretical Biological Oxygen Demand (ThBOD):	3.07 mg/L
Bioaccumulation:	Carp 13.5 BCF

Acute and Chronic Toxicity to Fish

LC50 9 mg/L/96 hr sheepshead minnow (cyprinodon variegatus) LC50 29 – 59.3 mg/L/96 hr fathead minnow (pimephales promelas) LC50 25 mg/L/96 hr bluegill (lepomis macrochirus) LC50 2.4 – 4.1 mg/L/96 hr rainbow trout (salmo gairdneri)

Acute Toxicity to Aquatic Invertebrates

EC50 4.7 – 23 mg/L/48 hr water flea (daphnia magna)

Toxicity to Aquatic Plants

EC50 1.4 mg/L/72 hr green algae (selenastrum capricornutum)

Toxicity to Microorganisms

EC50 approx. 500 mg/L/30 min activated sludge microorganisms EC50 5.5 mg/L/5 min photobacterium phosphoreum EC50 72 mg/L/16 hr pseudomonas putida

Section 13. Disposal Considerations

Disposal Methods

Product Recommendation:

1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.

2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14. Transportation Information			
UN Number:	Not Relevant		
UN Proper Shipping Name:	Not Relevant		
Transportation Hazard Class(es)			
DOT:	Not Regulated/classified		
TDG:	Not Regulated/classified		
ADR / RID:	Not Regulated/classified		
IMDG:	Not Regulated/classified		
ICAO/IATA	Not Regulated/classified		
Packing Group:	Not Applicable		
Environmental Hazards:	Not Relevant		
Transportation in Bulk (According t	o Annex II of MARPOL 73/78 and IBC Code):	Not Relevant	
Special Precautions for User:	No special precautions		

Section 15. Regulatory Information

(Not meant to be all-inclusive - selected regulations represented)

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See other sections for health and safety information.

US EPA CERCLA Hazardous Substances (40 CFR 302):

Components

Styrene 100-42-5 < 0.1% RQ=1000 lbs

SARA Section 311/312 Hazard Categories: Not Hazardous

US EPA Emergency Planning and Community Right to Know Act (EPCRA) SARA Title III

Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A): Components None

Section 313 Toxic Chemicals (40 CFR 372.65) – Supplier Notification Required: <u>Components</u> Styrene 100-42-5 < 0.1%

US EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents

If discarded in purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24).

State Right-to-Know Information

The following chemicals are specifically listed by individual states; other product specific data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists		
Weight%	Components	CAS-No.
>=1%	Acrylonitrile/Butadiene/Styrene Terpolymer	9003-56-9

Canadian Regulations

Canadian CEPA Status: All of the components of this product are listed on the DSL.

OSHA HazCom:	This Material is not Hazardous b OSHA Hazardous Communication Standard 29 CFR 1910.1200		
SARA 313:			
Immediate Hazard: NO		Fire Hazard: NO	Reactivity Hazard: NO
Delayed Hazard: NO		Pressure Hazard: NO	

Section 16. Other Information

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosion from the Manufacturing, Processing, and Handling of

NOTICE: The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: March 7, 2017