

SAFETY DATA SHEET

techhelp@rowmark.com

NEW GHS Hazard Categories

Category 1 = Severe Hazard

Category 2 = Serious Hazard

Category 3 = Moderate Hazard

Category 4 = Slight Hazard

Category 5 = Minimal Hazard

SDS No: 0025

Email:

Section 1. **Product and Company Identification** Product Name: Satins Trade Name: Acrylic Multipolymer, ABS Recommended Use: Signage, Other Restrictions on Use: None Medical:911 Manufacture: Rowmark In Case of Emergency: Call: Poison Control: 800-589-3897 5409 Hamlet Drive Email: Findlay, OH 45840 Information: Call: 1-877-ROWMARK

Section 2. Hazard Identification

GHS Classification: Not Classified
GHS Label Elements: Not Applicable

GHS Rating

Health	5
Flammability	4
Instability	5
Special	

Other Hazards: Not Applicable

Section 3. Composition / Information on Ingredients				
Name	CAS#	% by Weight	OHSA	
Titanium Dioxide	013463-67-7	0-4%	Υ	
Barium sulfate	007727-43-7	0-2%	Υ	
Acrylonitrile/butadiene/styrene resin	009003-56-9	90-100%		
May contian the following:				
Mineral oil	008042-47-5	0-2%		
Tallow	008030-12-4	0-2%		
Wax	000110-30-5	0-2%		

The substance(s) marked with a "Y" in the OSHA column are idenfitied as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The components of this product are all on the TSCA Inventory list.

Section 4. First Aid Measures

^{*} Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

Inhalation:	Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not				
	breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.				
Eyes:	Dust, fines and prod	cess vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes. Get			
	medical attention.				
Skin:	Exposure to molten	plastic may cause thermal burns. If molten material comes in contact with the skin, cool under ice			
	water or a running	stream.			
Ingestion:	No adverse health	effects expected from ingestion.			
Section 5.	Fire-Fighting M	easures			
Suitable Exting	uishing Methods:	Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on			
		molten burning material.			
Unsuitable Exti	nguishing Methods:	NONE known.			
Hazards During	Fire-fighting:	Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.			
Protective Equi	ipment:	Wear self-contained breathing apparatus and protective suit.			
Section 6.	Accidental Rele	ase Measures			
Personal Precautions:		See Section 8 - Exposure Controls / Personal Protection.			
Environmental Precautions:		No Special environmental precautions required.			
Methods and	Materials for Conta	inment and Cleaning Up			
Spill / Leak: Containment o		of this material should not be necessary. Sweep up or gather material and place in appropriate			
	container for disposal.				

Section 7.

Handling and Storage

Handling: Keep away fro	om heat, flame and strong oxidizing agents.	
Storage: Keep away fro	om heat, sparks, and flame. Store in cool place in origin	nal container and protect form sunlight.
Section 8. Exposure Contro	ol and Personal Protection	
Exposure Limits:		
1) Effects of Acute Exposure:	Inhalation of vapors may result in irritation of upper	respiratory tract
2) Effects of Chronic Over Exposure:		
3) OSHA Permissible Exposure Limits:	US. ACGIF Threshol	d Limit Values
	Form:	Inhalable particles
	Time weighted average	10 mg/m3
	Form:	Respirable particles
	Time weighted average	3 mg/m3
	US. OSHA Table Z-1 Limits for Air Cor	ntaminants (29 CFR 1910.1000)
	Form:	Respirable fraction
	PEL:	5 mg/m3
	Form:	Total dust
	PEL:	15 mg/m3
	US. OSHA Table Z-3 (29	9 CFR 1910.1000)
	Form:	Respirable fraction
	Time weighted average	15 ppm
	Form:	Total dust
	Time weighted average	50 ppm
	Form:	Respirable fraction
	Time weighted average	5 mg/m3
	Form:	Total dust

4) Carcinogen Potential:

Engineering Controls:

Use recommended safe handling practices to minimize unnecessary exposure.

General room ventilation is adequate for storage and ordinary handling.

Use local exhaust at points of fume generation or if dusty conditions prevail.

Personal Protective Equipment:

Wear safety glasses with side shields or chemical goggles to prevent eye contact.

Have eye-washing facilities readily available where eye contact can occur.

Wear impervious gloves and protective clothing to prevent skin contact.

Section 9. Physical and Chemical Properties				
Appearance:	Various Colors	Vapor Pressure:	Not Applicable	
Odor:	Slightly acrylic	Vapor Density:	Not Applicable	
pH:	Not applicable	Relative Density:	1.19 g/cm3	
Melting Point / Freezing Point:	No data available	Solubility (ies):	Not Applicable	
Boiling Point:	No data available	Partition Coefficient (N-Octanol/Water):	No data available	
Flash Point:	Not applicable	Auto-Ignition Temperature:	850°F (454°C)	
Evaporation Rate:	Not applicable	Decomposition Temperature:	>572°F (> 300°C)	
Flammability (solid, gas):	See GHS in section 2	Viscosity:	No data available	
Upper Explosive Limit:	Not applicable	Specific Gravity:	1.19 Water = 1 (liquid)	
Lower Explosive Limit:	Not applicable	Percent Volatile:	0%	

Section 10. Stability Reactivity			
Reactivity:	No data available		
Chemical Stability:	Stable		
Possibility of Hazardous Reactions:	Hazardous polymerization does not occur		
	Avoid flames, welding arcs, potential ignition sources, or other high temperature sources,		
Conditions to Avoid:	prolonged contact with acids, alkalis and strong oxidizing agents		
Incompatible Materials:	None under normal conditions of use		
Hazardous Decomposition Products:	Carbon oxides, Acrylates, Methacrylates, Hazardous organic compounds		
Combustion Products:	No data available		

Section 11. Toxicological Information

Irritation Effects

 Eye Irritation:	Solid particles may cause transient irritation from mechanical abrasion.
 Skin Irritation:	Not expected to cause skin irritation. Molten material may cause thermal burns.
 Inhalation:	Not a likely route of exposure. Process fumes may cause irritation.
Ingestion:	May cause a choking hazard if swallowed.

Data for PLEXIGLAS® DR®-101 ACRYLIC RESIN

Acute Toxicity

Dermal: Acute toxicity estimate > 5,000 mg/kg Inhalation: 4 h Acute toxicity estimate > 10 mg/L

Data for Acrylic copolymers (Proprietary)

Other Information

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

Data for Acrylic styrene copolymers (proprietary)

Other Information

The information presented is from a representative material with a similar structure. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

Additional Toxicological Information

When used and handled according to specifications, the product does not have any harmful effects according and information provided by suppliers.

to research

Carcinogenic Effect

International Agency for Research on Cancer (IARC): Group3 NOT classifiable as to its carcinogenicity to humans.

Section 12. Ecological Information				
Eco-toxicity:	Toxicity to fish - No relevant studies identified.			
Persistence and Degradability:	This material is not expected to be readily biodegradable.			
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.			
Mobility in Soil:	This Product has not been found to migrate through soils.			
	This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the			
Other Adverse Effects:	ozone layer.			

Section 13. Disposal Considerations

Disposal Methods

Product Recommendation:

- 1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
- 2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14. Transportation I	nformation	
UN Number:	Not Relevant	
UN Proper Shipping Name:	Not Relevant	
Transportation Hazard Class(es)		
DOT:	Not Regulated/classified	
ADR / RID:	Not Regulated/classified	
IMDG:	Not Regulated/classified	
ICAO/IATA	Not Regulated/classified	
Packing Group:	Not Applicable	
Environmental Hazards:	Not Relevant	
Transportation in Bulk (According to Ar	nex II of MARPOL 73/78 and IBC Code):	Not Relevant
Special Precautions for User:	No special precautions	

Section 15. Regulatory Information

(Not meant to be all-inclusive -- selected regulations represented)

Hazard categories under criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	N	Delayed (Chronic) Health	N
Sudden Release of Pressure	N	Reactive	N
Fire	N		

The components of this product are all on the TSCA inventory list.

INGREDIENT RELATED REGULATORY INFORMATION:

SARA REPORTABLE QUANTITIES	CERCLA RQ	SARA TPQ
Ethyl acrylate	1000 LBS	N/A
Methyl methacrylate	1000 LBS	N/A

P (EA/MMA) N/A N/A			
	P (EA/MMA)	N/A	N/A

SARA TITLE III, SECTION 313

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. See section 2.

Chemical Name	CAS-No.	De minimis concentration	Reportable Threshold:
Ethyl acrylate	Not assigned	Not assigned	Not assigned
Methy methacrylate	Not assigned	Not assigned	Not assigned
			10000 lbs (otherwise used (non-
			manufacturing/processing))
			25000 lbs (manufacturing and
2-Propenoic acid, ethyl ester	140-88-5	0.10%	processing)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)-Reportable Quantity (RQ)

Chemical Name	CAS-No.	Reportable quantity
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	1000 lbs
2-Propenoic acid, ethyl ester	140-88-5	1000 lbs

Chemical Inventory Status

EU. EINECS	EINECS	Conforms to
		The components of this product are all
United States TSCA Inventory	TSCA	on the TSCA Inventory
		All components of this product are on
Canadian Domestic Substnaces List (DSL)	DSL	the Canadian DSL.
China. Inventory of Existing Chemical		
Substances in China (IECSC)	IECSC (CN)	Does not conform
Japan. ENCS - Existing and New Chemical		
Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL-Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and		
Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances	AICS	Conforms to

OSHA HazCom:	This Material is not Hazardous b OSHA Hazardous Communication Standard 29 CFR 1910.1200			
SARA 313:				
Immediate Hazard: NO		Fire Hazard: NO	Reactivity Hazard: NO	
Delayed Hazard: NO		Pressure Hazard: NO		

Section 16. Other Information

No Additional Information

NOTICE: The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: March 7, 2017